

鹼錳干電池規格書
SPECIFICATIONS
FOR ALKALINE MANGANESE DRY BATTERY

LR61
(尖頭 Protrusive Cap)

接收人 RECEIVED BY :

制作人 Prepared by 

核準人 Approved by 

日期 Date : OCT 2024

松柏電池廠有限公司
CHUNG PAK BATTERY WORKS LIMITED
香港寫字樓:香港九龍油塘灣草園街四號華順工業大廈二樓B室
Unit B, 2/F., Wah Shun Industrial Building, 4 Cho Yuen Street, Yau Tong Bay,
Kowloon, Hong Kong
電話 TEL : (852) 27171338 傳真 FAX: (852) 27727727
電子郵件 E-MAIL: cpgsales@chungpak.com 網址 Website: www.vinnic.com

松柏(廣東)電池工業有限公司
CHUNG PAK (GUANG DONG) BATTERY INDUSTRIAL CO.,LTD
廠址: 中國廣東省佛山市順德區陳村鎮佛陳公路紺村路段
Gan Cun Section, Fo Chen Road, Chen Cun County, Shun De District, Fo Shan City, Guang Dong
Province, China
電話 TEL: (86 757) 23312338 傳真 FAX: (86 757) 23312339
電子郵件 E-MAIL: cpgsales@chungpak.com 網址 Website: www.vinnic.com

本公司保留更改產品規格書任何資料的權力，且無須預先通知。

We reserve all rights for the change of product specification and any information without any prior notice.

無汞鹼錳電池 Mercury Free Alkaline Manganese Battery LR61(尖頭 Protrusive Cap)


1. 範圍 Scope

該規格書適用於由松柏(廣東)電池工業有限公司提供之“Vinnic”——“銀戰士”商標無汞鹼錳幹電池。

This specification is applicable to the“Vinnic” brand Alkaline Manganese Mercury Free Dry Batteries supplied by **CHUNG PAK BATTERY WORKS, LTD.**

2. 基本信息 Essential Information

型號 Model	IEC/JIS LR8D425 ANSI AAAA
電化學體系 Electrochemical System	鋅-二氧化錳 Zinc/ MnO ₂
標稱重量 Nominal Weight	約 About: 6.6g
標稱電壓 Nominal Voltage	1.5 V
使用溫度 Usage Temperature	0℃~40℃
使用推薦期限 Recommended Life (保存條件 Storage condition 20±2℃, RH55+20/-40%)	5 years
外包裝和標識 Packaging and Mark	塑膠鋁膜 (標識有效期) Plastic label (aluminum jacket) marked with expiry date
重金屬含量 Content of heavy metals	Hg ≤ 1ppm Cd ≤ 20ppm Pb ≤ 40ppm
執行標準 Reference Standard	IEC 60086-2 IEC60086-5 (EU) 2023/1542



	尺寸(mm) Dimension
A	7.7-8.3
B	41.5-42.5
C	0.7 Min.
D	3.8 Max.

3. 電性能 Electrical Characteristics

如無特殊說明，以下所有的測試項目均在標準環境(20±2℃,RH55+20/-40%)下進行。

在測試之前，樣品應在測試環境(20±2℃,RH55+20/-40%)中存放至少8h。

Unless otherwise specified, all of the following tests are carried out under the standard environment (20±2℃,RH55+20/-40%).

Before testing, the sample should be stored in the test environment (20±2℃,RH55+20/-40%) for at least 8h.

3.1 開路電壓、閉路電壓及短路電流 (負載電阻30Ω、短路時間0.08s)

Open circuit voltage, Closed circuit voltage and Short-circuit current
(Load resistance 30Ω, short-circuit time 0.08s)

(Load Resistance 501Ω, Short-circuit time 0.005s)		
初期 Initial	項目 Item	MAD
	開路電壓OCV	1.60V
	負載電壓CCV	1.30V
	短路電流SCC	4A

備註 Remark : MAD: 最小平均值 Minimum Average Duration

無汞鹼錳電池 Mercury Free Alkaline Manganese Battery LR61(尖頭 Protrusive Cap)

3.2 放電性能 Discharge Performance

序號 No.	模擬用電器 Appliances simulating	放電制度 Discharge Pattern	終止電壓 End Voltage	單位 Unit	MAD	水平值 Level value
1	手電筒 Portable lighting	5.1Ω-5min/d	0.9V	min	105.0	115.0
2	激光筆 Laser pointer	75Ω-1h/d	1.1V	hour	26.0	30.0
3	放電量檢驗 Service output test	75Ω-1h/d	0.9V	hour	35.0	38.0

備註 Remark:

- 1)MAD: 最小平均值 Minimum Average Duration (代表電池能達到的最低性能水平 Represents the battery can achieve the lowest level of performance)
- 2)水平值 Level value: 代表電池的長期測試水平, 某批次的電池放電結果可能在水準值上下波動。 Represents the long term level of the battery, and the battery discharge results of a lot may above and below the level value.

4. 耐漏液性能 Leakage Resistance

序號 No.	測試項目 Test Item	測試方法 Test Method	樣品數量 Sample Size	標準
1	高溫高濕試驗 High Temperature and humidity Test	將滿足本規格書 3.1 條款的電池在 60±2℃,RH90±5%的環境下儲存一定時間, 取出後於常溫條件放置 4~24h 後檢查。 The battery meet 3.1 of this specification. Store at 60±2℃, RH90±5% for a period of time. Check after store at room temperature for 4~24h.	10 pcs	20 天無漏液 No leakage after store for 20 days

5. 安全性能 Safety Performance

進行本測試項目的電池樣品應該滿足本規格書的3.1條款。同時, 如無特殊說明, 以下所有的測試項目均在標準環境(20±2℃,RH55+20/-40%)下進行。電池的儲存條件均為標準環境((20±2℃, RH55+20/-40%)。在測試之前, 樣品應在測試環境(20±2℃,RH55+20/-40%)中存放至少8h。
The battery sample for test item should meet 3.1 of this specification. Unless otherwise specified, all of the following tests are carried out in the standard environment (20±2℃,RH55+20/-40%). The storage condition is the standard environment (20±2℃,RH55+20/-40%). Before testing, the sample should be stored in the test environment (20±2℃,RH55+20/-40%) for at least 8h.

序號 No.	測試項目 Test Item	測試方法 Test Method	樣品數量 Sample Size	標準
1	電池部分使用后貯存 Partial use	具體測試方法參考 IEC 60086.5 執行 Specific test method refer to IEC 60086.5	5 pcs	無漏液、無爆炸、無著火 No leakage, No explosion No fire
2	運輸-振動 Transportation-vibration		5 pcs	無漏液、無爆炸、無著火 No leakage, No explosion No fire
3	運輸-冲击 Transportation-shock		5 pcs	無漏液、無爆炸、無著火 No leakage, No explosion No fire

無汞鹼錳電池 Mercury Free Alkaline Manganese Battery LR61(尖頭 Protrusive Cap)

(续上表 Continued)

序號 No.	測試項目 Test Item	測試方法 Test Method	樣品數量 Sample Size	標準
4	熱循環 Climatic	具體測試方法參考 IEC 60086.5 執行 Specific test method refer to IEC 60086.5	5 pcs	無爆炸、無著火 No explosion, No fire
5	不正確安裝 Incorrect installation		5 組 5 groups	無爆炸、無著火 No explosion, No fire
6	外部短路 External Short-Circuit		5 pcs	無爆炸、無著火 No explosion, No fire
7	過放電 Over discharge		5 組 5 groups	無爆炸、無著火 No explosion, No fire
8	跌落 Free fall		5 pcs	無爆炸、無著火 No explosion, No fire

6. 使用電池安全注意事項 (具體安全存放等事項可參考 IEC60086.5 執行) USAGE GUIDE (Please refer to IEC60086.5 for detailed safety and storage specifications.)

6.1 請按電池及用電器具上標明的極性標誌(“+”和“-”)正確裝入電池；

Insert batteries correctly with regard to the polarities (“+”/“-”) marked on the battery and the electrical appliances;

6.2 請勿將電池短路、充電、加熱、投入火中、強制放電或拆卸破壞；

Do not short-circuit, recharge, heat, disassemble the battery, or dispose of in fire;

6.3 請勿將新舊電池或不同類型、不同牌號的電池混合使用；

Do not mix use old batteries with new ones, or mix use batteries of different types or brands;

6.4 請及時從用電器具中取出電量已經耗盡的電池；

Remove the exhausted battery from the appliances immediately;

6.5 電池應存放在兒童拿不到的地方，無人監督時不要讓兒童更換電池；


Keep the batteries away from small children; do not let the child remove/ replace batteries without monitoring from adults.

6.6 電池的保存環境在15-25℃之間，不應當超過30℃，並應避免存儲在極端濕度環境下(濕度範圍應控制在RH40%-95%)，光身電池建議貼標後保存。

Storage condition of the batteries shall be: Temperature 15℃~25℃ (no higher than 30 ℃), while extremely damp environment beyond RH: 40%~95% shall be avoided.

無汞鹼錳電池 Mercury Free Alkaline Manganese Battery LR61(尖頭 Protrusive Cap)

7. Brand and Packaging



用透明膠帶、PP 打包帶封箱 Seal carton by transparent tape and PP strap

紙箱內共 3366 只電池 There are 3366 pcs LR61 in carton

紙箱外尺寸 Carton dimension: 452*257*142(mm)

毛重 Gross weight: 23.1kg

堆碼 Stacking: 6 層/Layers

包裝規格 Packaging Specification

序號 Type	名稱 Name	用量/電池數量 Dosage / Battery Quantity	規格 Specification
1	單層標貼 (PVC 或 PET) Single layer label (PVC or PET)	1 piece/1pc	LR61
2	瓦楞墊板 Corrugated board	3 pieces/1683pcs	407*214mm
3	防潮紙 Moisture proof paper	2 pieces/1683pcs	400*210mm
4	紙托盤 Paper pallet	1 /1683pcs	430*237*54mm
5	包裝紙箱 carton	1 /3366pcs	/
6	塑料包裝袋 Plastic package bag	1/3366pcs	810*720*0.03mm
7	運輸唛頭 Shipping mark	/	90*40mm
8	PP 打包帶 PP straps	2.5m/3366pcs	13.5*1.0mm
9	透明膠帶 Transparent tape	1.2m/3366pcs	55mm*90m